



ROYAL NOISE REFLECTOR

PANEL MANUFACTURED
WITH THE USE OF RAB2 TECHNOLOGY

Panels properties comply with Technical Approval n° AT/2008-03-2344/2:

- Resistance to wind load zone I and II according to PN-B-02011; TA p. 3.3
- Resistance to dynamic loads associated with snow clearance max 50 km/h according to PN-EN 1794-1; TA p. 3.3
- Resistance to stone strokes met according to PL-EN 1794-1; TA p.4, tab. 2, p. 34
- Resistance to UV rays met; TA p. 4, tab. 2, p. 8
- The panels are marked with the CE sign


Cases are manufactured in the following dimensions:


- length up to 4960 mm
- height up to 333 mm and as a filling 167 mm
- thickness 100 mm

The panels end with system gaskets fitting with various pole types (double-tee bars 140, 160 and 180).

RAB cases possess specifically shaped upper and lower surfaces allowing to easy installation into blade and gully, whereas their relatively light construction (around 16 g/m2) enables the assembly with no heavy equipment.

Tested properties	Test results			NOTES	
Specific acoustic resistance	Rw (C, Ctr)	DLr	class	No mineral wool	
Royal Noise Reflector	27 (-1, -3)	25	В3		
Acoustic absorption coefficient		DLα	class	No mineral wool	
Royal Noise Reflector		1	Al	No mineral Wool	







Polymer panels do not require maintenance and painting.

Graffiti can be easily removed from the panels' surfaces with the use of anti-graffiti agents available in the market.

In case of use of identical panels any additional costs protecting against graffiti are not incurrred.

The panels are in-mass colored in the extrusion process according to the manufacturer's palette.





Zittau and Hradek nad Nisou road link.



Working plans and specifications of acoustic baffle and its construction within GPO Zopowy station (parcel n° 34/9, ul. Polna, Głubczyce).

Zittau and Hradek nad Nisou road link.



World Acoustic Group SA

UL. ROYAL 1, 59-101 POLKOWICE, POLAND NIP: 692-22-60-445, KRS: 0000373208

WWW.WAGSA.EU